

# How to use the Accordion style TAB-CONTROL.

## User Interface

Starting with the 2016R1 release, isCOBOL provides support for the ACCORDION-style TAB-CONTROL.

This feature can be enabled by applying the ACCORDION style to a TAB-CONTROL element. When this style is active, the tab-group associated with each tab are displayed only when their corresponding tab item is selected. The behavior mimics an accordion layout: selecting an item expands its associated content while collapsing the previously active section.

Here's a code example:

```
03 Tb1-accordion tab-control    line 2 col 2 lines 17 cells size 68
cells    accordion. 03 tb1-accordion-page1    tab-
group Tb1-accordion tab-group-value 1.    05 label
      ... 03 tb1-container-page2    tab-group
Tb1-accordion tab-group-value 2.    05 label      ...
```

The image shows the final result with the ACCORDION style set on TAB-CONTROL. You can see the full sample program in %ISCOBOL%/sample/issamples under GUI controls, TAB-CONTROL, Accordion

TAB Control accordion

Page1

Page2

Songs

This is the third page

After Midnight	Eric Clapton
Albachiara	Vasco Rossi
Angie	The Rolling Stones
Bad Love	Eric Clapton
Bollicine	Vasco Rossi
C'e' chi dice no	Vasco Rossi
Foo Foo	Santana
Help!	Beatles

[View Source \[F2\]](#)

[Exit](#)

Online URL: <https://support.veryant.com/phpkb/article.php?id=278>