

How to use font-based icons in isCOBOL GUI programs

When your GUI application is going to need a large variety of different bitmaps for any kind of GUI control that accepts a bitmap for its icon, you can use font-based bitmaps instead of trying to get different images for each control. Bitmap fonts provide a comprehensive set of glyphs, or icons.

In this article we will use one of the most popular bitmap fonts: **FontAwesome**. You can download it from: www.fontawesome.com.

However, any bitmap font can be used (Material Design Font, dafont.com, etc)

The .otf file that you download can be located in any folder that you choose. You create a named font with W\$CREATEFONT that points to the path (full or relative) of the font.

```
move "Font Awesome 5 Free Solid" to font-name  call "w$createfont" using  
"files/Font Awesome 5 Free-Solid-900.otf"           font-name
```

Then you load a font with W\$FONT based on that named font.

```
initialize wfont-data  set wfdevice-console to true  move font-name      to wfont-  
name  move 10          to wfont-size  call "w$font" using wfont-get-font      h-  
font          wfont-data
```

Now, in order to use some of the icons from that font for your program, you need to create a strip of selected icons.

The FontAwesome font uses a hexadecimal code of 4 characters to refer to their icons.

Here's a link to all of the available icons and their hex codes:

<https://fontawesome.com/v5/cheatsheet>

Each of those hex codes need to be converted to a decimal value and then combined in a national variable as in this example:

```
77 character-1-hex      pic x(4). 77 character-1-n      pic n(1). 77  
character-1-red      pic x(2) comp-x  
                           redefines character-1-n. ... 77 icon-  
characters      pic n any length. ...  move "f1c3" to  
character-1-hex  move "f576" to character-2-hex  move "f008" to  
character-3-hex  move function hex2dec(character-1-hex) to  
character-1-red  move function hex2dec(character-2-hex) to  
character-2-red  move function hex2dec(character-3-hex) to  
character-3-red  initialize icon-characters  string  
character-1-n delimited by space  
                           character-2-n delimited by space  
                           character-3-n delimited by space      into icon-characters.
```


Once you have the list of decimal values in a national string, you can create the bitmap strip in memory, using the W\$BITMAP routine:

```
call "w$bitmap" using wbitmap-load-symbol-font,  
characters          20          icon-color          h-font  
                           icon-giving h-font-icon          icon-
```

Now, since the h-font-icon handle of font contains the strip of icons 20 pixels each, you can assign icons from it to a GUI control on the screen section:

03	ef-1	entry-field	line	5	col	15	size
icon		20 cells	lines	2 cells	bitmap-handle		h-font-
pb-1	push-button	line		9	col	15	lines
icon		2 cells	size	20 cells	bitmap-handle		h-font-
		bitmap-width	20	title-position	2	title	
		"Option A"	bitmap-number	2			

This code creates part of a simple example screen that looks like this:



Attached is a zip file with a full sample of using the FontAwesome bitmap font. After downloading it, you can compile:

```
iscc fontawesome.cbl
```

and run:

```
iscrun FONTAWESOME
```

Online URL: <https://support.veryant.com/phpkb/article.php?id=325>